



DDK-1600D

Indoor Mini IP Dome Camera

Key Features & Benefits

- Compact Form-Factor
- Dual-Codec, M-JPEG / MPEG-4
- 1/3" CCD, D1 Resolution
- 3.5-8mm Varifocal Lens
- PoE Ready
- 96 Zone Motion Detection Alarm I/O
- Multi-Zone Privacy Masking
- Analog Video Output
- Free 32-Channel NVR Video Recording Software



Technical Specifications

Image Sensor	Sony 1/3" CCD	Alarm/I/O/Reset	1/1/1
Compression	M-JPEG / MPEG-4 Selectable	Power Requirement	12V DC / PoE
Camera Resolution	420 TV Lines	Power Consumption	350 mA
Video Adjustments	Max AGC, Contrast, Brightness, BLC, Saturation, Sharpness, Flickerless	Weight	13 oz. (369 grams)
Exposure	AGC / AWB	Dimensions	4.33" (H) x 4.65" (D) 110 (H) x 118 (H) mm
Electronic Shutter	1/60 - 1/100,000 sec	Operating Temperature	0C – 50C (32F – 122F)
Sensitivity	Color: 1 lux @ F1	Approvals	FCC, CE, RoHS
Lens	3.5-8 mm Varifocal Manual Iris	Network Interface	Ethernet 10/100 Base-TX, MDIX
MPEG-4 Resolution	Full D1, Half D1, CIF	Network Protocol	TCP/IP, DHCP, HTTP, UDP, FTP, SNTP, ICMP, DDNS, DNS, UPnP, PPPoE, ARP
MPEG-4 Frame Rate	30, 24, 15 fps		
MPEG-4 Bitrate	Multi-Level, 64Kbps - 8Mbps		
Motion Detection	96 zones, 5 levels		
Privacy Masking	3 Zones		
Time Stamp	Time/Date/Title		
Digital Signature	M-JPEG Watermark		
Password Authorization	Multi-level / Multi-users		
Video Output	1.0 VpP, 75 ohm, composite		

Product specifications and availability subject to change without notice.

IPX International, Inc. : 12 Christopher Way, Suite 200
 : Eatontown, NJ 07724
 : Tel. 866-323-9647
 : Fax 732-333-1446